

DLSE4-MCT

Customer Name: _____

Project Name: _____

Note: _____



Type: _____



Selection:



MCT



6 1/5" x 1"

Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

Features

- Spun Steel, Powder-Coated
- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Damp Location Performance
- MCT: The Switch is On The LED Board Under The Lens
- White Translucent Acrylic Lens
- 5-Year Warranty
- JA8-E-2016 & Title 24 Compliant (approved approved by the state of California and registered with the California Energy Commissions (CEC))

Technical Specifications

Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 9W
- Efficacy: 60 LPW

Mechanical:

- White Finish
- Spun Steel, Powder-Coated
- Fits on 4" Octagonal (4O) or 3" Octagonal (3O) Electrical Boxes
- Maximum Ambient Temperature: 104°F
- Rated life: 50,000 hrs
- Suitable for Damp Location

Lighting:



- Lens: White Translucent Acrylic
- MCT: The Switch is On The LED Board Under The Lens
- LED: Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Damp Location Performance
- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Total Lumens: 540LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Color Rendering Index: CRI ≥ 90

Applications:


- Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications



Photometrics: DLSE4-MCT



BUG Rating: B0-U1-G0




Area 30' x 30' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: DLSE4-MCT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
DLSE4-MCT	9W	120V	540LM	3000K 4000K 5000K	B0-U1-G0	60

Sample Ordering

Model Color Temp.

DLSE4 - MCT

Example:

1. DLSE4-MCT

(FOR DLSE4 9W MCT FIXTURE 120V)

