



DIMENSIONS:

FML-R8-14W-30K
FML-R8-14W-50K

LED FLUSH MOUNT SURFACE FIXTURE (8")

The LED Flush Mount Surface Fixture is a low profile downlight intended for ceiling or wall mount applications. Driver on Board (DOB) technology, with no driver or transformer needed. These flush mount ceiling lights mount directly to a 4" deep dish junction box. provides general LED illumination in residential and light commercial applications.

FEATURES:

- Driver on Board Technology provides a 120V alternating current source and eliminates the need for traditional LED driver.
- Quick and easy to install on standard junction box, wall or ceiling mount with mounting plate
- Die-cast aluminum housing, high transmittance lens allowing for smooth, comfortable light pattern

ELECTRICAL SPECIFICATIONS:

- Voltage: 120V AC
- Wattage: 14W
- Lumens: 750LM
- Color Temperatures: 3000K and 5000K
- Maximum Ambient Temperature: 104°F
- CRI: 90+
- Power Factor: 0.95

| MODEL | WATTS | VOLTS | LUMENS | COLOR TEMP |
|----------------|-------|-------|--------|------------|
| FML-R8-14W-30K | 14W | 120V | 750LM | 3000K |
| FML-R8-14W-50K | 14W | 120V | 750LM | 5000K |

LIGHTING SPECIFICATIONS:

- Dimmable down to 10% using an approved dimmer
- LED: Epistar
- Life span: 50,000 hours
- Suitable for Damp Locations when gasket

HOUSING SPECIFICATIONS:

- Housing: Die-cast aluminum
- Finish: Powder coated white
- Diffuser: Matte white polycarbonate
- Gasket: Close cell Neoprene foam gasket
- Optics: White translucent acrylic lens

WARRANTY: 5 years

CERTIFICATIONS:

