


# LLHB4 SERIES Industrial Lighting

LLHB4-150W-MP-40K-D-480V  
LLHB4-150W-MP-50K-D-480V  
4TH GENERATION OF LINEAR HIGH BAYS



Ideal for replacement of conventional lighting systems such as HID and fluorescent. Applications include manufacturing warehousing and other large indoor spaces with mounting heights from 10ft. to 40ft. the fixture can be surface mounted also.

Customer Name: \_\_\_\_\_  
Project Name: \_\_\_\_\_  
Note: \_\_\_\_\_ | Type: \_\_\_\_\_



24 1/4" (L) X 17 3/4" (W) X 2" (H)

## Features

- High Quality LED Chips To Provide High Efficiency, Heat Dissipation
- Stability, And Lumen Maintenance.
- Polycarbonate Lens, High Flame Retardant Point
- 50,000 Hours Rated Life
- 5-Year Warranty
- Multi-Power: The Switch Is On The Driver

## Technical Specifications

### Electrical:

- Voltage: 480V
- Wattage: 80W/110W/150W
- Power Factor: >0.95
- Efficacy: 136 LPW

### Mechanical:

- Surge Protector
- Steel Housing
- Steel Thickness: 24 Gauge
- V-Hooks
- Unprecedented Quality.
- Aluminum LED Board
- Operating Temperature: -4°F ~ 131°F
- Suitable for Damp Locations

### Lighting:

- Multi-Power: The Switch Is On The Driver
- Dimming: 0~10V Dimmable
- Lens: Polycarbonate Lens
- Total Lumens: 20400LM (Per Industry Standards, Lumens Are Reported Without Frosted Lens)
- Color Temperatures: 4000K and 5000K
- Color Rendering Index: >80
- Wide Beam Angle

### Applications:



- Warehouse
- Manufacturing Plants Distribution Centers
- Industrial Commercial
- Grocery Stores Gymnasiums

### Other Models:


- 100W | 13600LM | LLHB4-100W-MP-40K-D-480V
- 100W | 13600LM | LLHB4-100W-MP-50K-D-480V



## Photometrics: LLHB4-150W-MP-D-480V



BUG Rating: B4-U3-G2



## Other Views:



Front View



Side View



Back View

## Performance Table: LLHB4-150W-MP-D-480V

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LLHB4-150W-MP-40K-D-480V	150W	480V	20400LM	4000K	B4-U3-G2	136
LLHB4-150W-MP-50K-D-480V				5000K		

## Sample Ordering

Model	Wattage	Color Temp.	Dimming	Voltage
LLHB4	150W	MP	D	480V
		40K = 4000K 50K = 5000K		

## Accessory Options

SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 10FT. 1/16" SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS  
 SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 20FT. 1/16" SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS  
 LLHB4-RODKIT = OPTIONAL ROD KIT, 3-1/4" DIA. X 40" H  
 WEC-2MD-35 = SENSOR COMPONENT  
 LLHB4-150W-WG = WIRE GUARD FOR 150W  
 LLHB4-SMK = SURFACE MOUNTING OPTION

## Factory-Installed Options

Blank = No Option  
 OPT-SEN-LLHB4 = MICROWAVE Bi-Level SENSOR  
 OPT-EM-HB4EXT = EXTERNAL EMERGENCY BATTERY BACKUP  
 OPT-FWH-63 = 6FT 3-WIRE WHIP  
 OPT-FWH-65 = 6FT 5-WIRE WHIP  
 OPT-FWH-66 = 6FT 6-WIRE WHIP  
 OPT-HBC-125TL-WH = 8FT, 15A, 125V, WHITE  
 OPT-HBC-277TL-WH = 8FT, 15A, 277V, WHITE  
 OPT-HBC-125SB-WH = 10FT, 15A, 125V, 18/3STR, WHT


## ACCESSORIES:



SCL-GSY10  
SCL-GSY20



LLHB4-150W-WG  
(Fixture Shown with  
LLHB4-150W-WG)



LLHB4-RODKIT  
(Fixture Shown with  
LLHB4-RODKIT)



WEC-2MD-35  
(Fixture Shown with  
WEC-2MD-35)



LLHB4-SMK  
(Fixture Shown with  
LLHB4-SMK)

## FACTORY-INSTALLED OPTION:



OPT-EM-HB4EXT



OPT-SEN-LLHB4

