LVS SERIES Indoor Lighting

LVS-24-MCT5-BK


SLIM ROTATABLE VANITY LIGHTS AND SCONCES



This is LED Vanity Model Ideal for office, Retail Store, Showroom, Residential applications and Damp environment lighting applications.



Customer Name:	
Project Name:	
Note:	Туре:



24"(W) x 4"(H)

Features

- Corrosion and Heat Resistance Powder Coated
- Finish: Black
- Durable Die-cast Aluminum

- Lens Type: Polycarbonate Lens
- MCT: Multi Color Temperature (Selectable Switch Inside Fixture)

Technical Specifications

Electrical:

Voltage: 120V AC 50/60Hz

Wattage: 20WPower Factor: >0.95

Total Harmonic Distortion: ≤ 20 %

Efficacy: 70 LPW

Mechanical:

- Corrosion and Heat Resistance Powder Coated
- Finish: Black
- Durable Die-cast Aluminum
- 180-Degree Rotatable Light Bars
- Operating Temperature: -22°F to 104°F
- IP20, Suitable for Damp Location
- 5-Year Warranty

Lighting:

- Multi-CCT(Selectable Switch Inside Fixture)
- Lens Type: Polycarbonate Lens
- Dimming: TRIAC Dimming (Dimmable Down to 5% Compatible With Traic and ELV Dimmers)
- Total Lumens: 1400LM
- Color Temperatures: 2700K/ 3000K/3500K/4000K/5000K
- Color Rendering Index: CRI ≥ 90
- 50,000 Hours Rated Life
- Beam Angle: 104.8°(H) x 100.5°(V)

Applications:

 Ideal for Office, Retail Store, Showroom, Residential Applications and Damp Environment Lighting Applications

Other Models:

20W | 1400LM | LVS-24-MCT5-BN
20W | 1400LM | LVS-24-MCT5-BB











Photometrics: LVS-24-MCT5-BK





Other Views:







Performance Table: LVS-24-MCT5-BK

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LVS-24-MCT5-BK	20W	120V	1400LM	2700K 3000K 3500K 4000K 5000K	B1-U3-G1	70

Sample Ordering

Model Size Color Temp. Housing

LVS = 24 = MCT5 = BK

Example:

1. LVS-24-MCT5-BK

(For LVS 20W MCT5 fixture 120V)

Other Model:





LVS-24-MCT5-BN

LVS-24-MCT5-BB