

SCX SERIES

Commercial Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!


SCX-4FT-40W-30K-D
SCX-4FT-40W-35K-D
SCX-4FT-40W-40K-D
SCX-4FT-40W-50K-D



Custom:  Selection:

Linear Lighting can be customized to your desired length, look & color temperature can either be suspended, surface, mounted or recessed to suit your needs. Ideal for Storage rooms, Offices Conference rooms, Retail Reception areas, Hallways Education facilities, hotels, and restaurants.

Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



47 2/5" (L) x 2 6/8" (W) x 3 3/8" (H)

Features

- LED Superior Architectural Lights
- Seamless Linkable Linear Lighting System
- Opal Polycarbonate Lens-Direct (DOWN) Lighting
- Optional Recessed & Wall Mounting Kits Available
- 50,000 Hours Rated Life
- 5-Year Warranty
- Lens Type: Opal Polycarbonate Lens
- Optional Louver Version Lens Available

Technical Specifications

Electrical:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 40W
- Power Factor: >0.95

Mechanical:

- Low Profile Modern Design
- Aluminum Housing With Matte White Finish
- Custom Colors Available
- Lens Snaps into Housing
- Make Different Connections Via T/L/X Joints on Both Ends
- Mounting Options: Surface, Suspended, Wall, Recessed
- IP Rating: IP54
- Operating Temperature: -13°F~104°F

Lighting:

- Dimmable: 0~10V Dimming
- Total Lumens: 4480LM/4600LM/4720LM/4840LM
- Color Temperatures: 3000K/3500K/4000K /5000K
- Color Rendering Index: CRI ≥ 80
- Up Light Option Available
- Beam Angle: 104.8°(H) x 100.5°(V)

Applications:

- Ideal for offices, hotels, corridors, saloons, libraries, meeting rooms, conference halls, and the best solution for modern lighting solutions
- It can be used in any indoor applications

Other Models:

• 20W | 2240LM | SCX-2FT-20W-30K-D • 30W | 3360LM | SCX-3FT-30W-30K-D • 60W | 6720LM | SCX-6FT-60W-30K-D • 80W | 8960LM | SCX-8FT-80W-30K-D
• 20W | 2300LM | SCX-2FT-20W-35K-D • 30W | 3450LM | SCX-3FT-30W-35K-D • 60W | 6900LM | SCX-6FT-60W-35K-D • 80W | 9200LM | SCX-8FT-80W-35K-D
• 20W | 2360LM | SCX-2FT-20W-40K-D • 30W | 3540LM | SCX-3FT-30W-40K-D • 60W | 7080LM | SCX-6FT-60W-40K-D • 80W | 9440LM | SCX-8FT-80W-40K-D
• 20W | 2420LM | SCX-2FT-20W-50K-D • 30W | 3630LM | SCX-3FT-30W-50K-D • 60W | 7260LM | SCX-6FT-60W-50K-D • 80W | 9680LM | SCX-8FT-80W-50K-D





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-Z5-ZB-22

Photometrics: SCX-4FT



BUD Rating: B2-U3-G1




Area 50'x 50' Mounting Height: 9'

Other Views:



Front View



Side View



Back View

Performance Table: SCX-4FT

| MODEL NO. | Wattage | Voltage | Lumens | Color Temp. | BUG Rating | LPW |
|-------------------|---------|----------|--------|-------------|------------|-----|
| SCX-4FT-40W-30K-D | 40W | 120~277V | 4480LM | 3000K | B2-U3-G1 | 112 |
| SCX-4FT-40W-35K-D | 40W | 120~277V | 4600LM | 3500K | B2-U3-G1 | 115 |
| SCX-4FT-40W-40K-D | 40W | 120~277V | 4720LM | 4000K | B2-U3-G1 | 118 |
| SCX-4FT-40W-50K-D | 40W | 120~277V | 4840LM | 5000K | B2-U3-G1 | 121 |

Sample Ordering

| Model | Size | Wattage | Color Temp. | Feature |
|-------|------|---------|-------------|---------|
| SCX | 4FT | 40W | | D |

30K = 3000K
35K = 3500K
40K = 4000K
50K = 5000K

Accessories:

Blank = No Option For Accessories

SCL-CS1-6FT = ADJ. 6FT 1/16in SINGLE SUSPENSION CANOPY SET WITH KEYHOLE END CONNECTOR, NON-POWER SIDE

SCL-CS1P-6FT = ADJ. 6FT 1/16in SINGLE SUSPENSION CANOPY SET WITH KEYHOLE END CONNECTOR, POWER SIDE WITH SJTW18/5 WHITE CORD

SCL-CS1P-6FT-NC = ADJ. 6FT 1/16in SINGLE SUSPENSION CANOPY SET WITH KEYHOLE END CONNECTOR

SCL-GS10 = ADJ. 10FT 1/16in DOUBLE SUSPENSION CABLE WITH SINGLE KEYHOLE CONN., LOOP GRIPPER ON TOP

SCL-GS20 = ADJ. 20FT 1/16in DOUBLE SUSPENSION CABLE WITH SINGLE KEYHOLE CONN., LOOP GRIPPER ON TOP

SCL-6FT-SJTW18/5 = 6ft White Cord, SJTW 18 AWG 5-Conductor (Black, White, Green + Purple & Gray for 0-10V Dimming)

SCL-6FT-SJTW18/5-100FT = 100ft Roll of White Cord, SJTW 18 AWG 5-Conductor (Black, White, Green + Purple & Gray for 0-10V Dimming)

SCL-6FT-SJTW18/5-100FT-BK = 100ft Roll of Black Cord, SJTW 18 AWG 5-Conductor (Black, White, Green + Purple & Gray for 0-10V Dimming)

SCL-6FT-SJTW18/6-100FT = 100ft Roll of Black Cord, SJTW 18 AWG 6-Conductor (Black, White, Green + Purple & Gray for 0-10V Dimming + Red for Backup Invertor)

SCL-AH = Heavy-Duty Auxiliary Hook for Up To 1/16" Aircraft Cable

SCL-ASC-500FT = 1/16" 500 ft. Steel Aircraft Cable Suspension

* More Mounting Options Refer to page 4

Factory-Installed Options:

Blank = No Option For Accessories

OPT-HBC-125BS-WH = 10FT, 15A, 125V, 18/3 STR, WHT

* More Factory-Installed Options Refer to page 6

SUSPENDED MOUNTING ACCESSORIES (NOT INCLUDED)



SCL-CS1-6FT SCL-CS1P-6FT SCL-CS1P-6FT-NC SCL-GS10 SCL-GS20



SCL-6FT-SJTW18/5-100FT



SCL-6FT-SJTW18/5-100FT-BK



SCL-ASC-500FT



SCL-AH



SCL-ASC-500FT



SCL-6FT-SJTW18/5

FACTORY-INSTALLED OPTIONS:




OPT-HBC-125BS-WH

Example:

- SCX-4FT-40W-40K-D (For SCX 40W 4000K fixture 120-277V)
- SCX-4FT-40W-40K-D OPT-HBC-125BS-WH (For SCX 40W 4000K fixture 120-277V) (10FT, 15A, 125V, 18/3 STR, WHT)



MOUNTING AND MODULES OPTIONS:



Recessed Mounted
(Flanged)



Surface Mounted




Wall Mounted



Suspended




T-Bar Installation




Flangless Recessed Mounted
(Mud-In)



Louver Kit Option



Color of Your Choice




L Module
(page 7)

- SCX-L-30K
- SCX-L-35K
- SCX-L-40K
- SCX-L-50K



T Module
(page 7)

- SCX-T-30K
- SCX-T-35K
- SCX-T-40K
- SCX-T-50K



X Module
(page 8)

- SCX-X-30K
- SCX-X-35K
- SCX-X-40K
- SCX-X-50K



Inside Corner Module
(page 8)

- SCX-IC-30K
- SCX-IC-35K
- SCX-IC-40K
- SCX-IC-50K




120° Corner Module
(page 9)

- SCX-C120-30K
- SCX-C120-35K
- SCX-C120-40K
- SCX-C120-50K



Suspension Rod Kit

- SCL-RS-12 12"
- SCL-RS-18 18"
- SCL-RS-24 24"
- SCL-RS-36 36"
- SCL-RS-48 48"



Up Light Option


- 3000K
- 3500K
- 4000K
- 5000K
- Blue
- Green



MOUNTING OPTIONS:


FLANGLSS RECESSED INSTALLATION IN WOOD CEILING

No additional accessories required.
 Make recessed preparations by installing a horizontal plank of wood on top of the wood ceiling at a recessed height of 3 3/8".
 Screw and anchor kit provided with each fixture can be used to fasten the top of the fixture to the wood plank through the holes on top of the fixture.
 You can also install vertical wood boards on top of the ceiling at the edge of the opening and open the fixture and put screws through the side of the fixture housing to fasten it to the wood boards.




SUSPENSION ROD KITS (SET OF 2)

| Model | SIZE |
|-----------|-------|
| SCL-RS-12 | 12 IN |
| SCL-RS-18 | 18 IN |
| SCL-RS-24 | 24 IN |
| SCL-RS-36 | 36 IN |
| SCL-RS-48 | 48 IN |




WALL MOUNTING

| Model | DESCRIPTION |
|----------------|--|
| OPT-SCX-WM-4FT | Install this optional wall mounting brackets on the back of the fixture. Connection cables will enter the fixture through one of these wall-mounting brackets. On your purchase order, please specify the position of where your wire entry from the wall. |



RECESSED MOUNT WITH FLANGE

| Model | DESCRIPTION |
|-----------------|---|
| OPT-SCX-FMR-4FT | Order this option and the fixture will be equipped with a 1/2" wide flange on four sides. Advanced design toggle-style brackets will also be provided, to adjust and hold the fixture against drywall or other hard ceilings from the top. When linking to another fixture or corner module, call us or send a copy of your plan along with your PO, and flanges will be removed on those ends that need to make a seamless connection. |




LINKING

| Model | DESCRIPTION |
|--------------------|--|
| OPT-SCX-LINKWIRING | Fixtures are equipped with pre-installed linking brackets and accessories and only need to be wired together. to receive a fixture prewired for linking, order the option below for each link to another fixture or a corner module. |



FLANGELESS RECESS MOUNT IN DRYWALL (MUD-IN)

| Model | DESCRIPTION |
|-----------------|--|
| OPT-SCX-MIF-4FT | Order this option and the fixture will be equipped with mud-in brackets on all four sides, mounted at 1/16" from the lens surface (specify if other spacing is needed). Advanced design toggle-style brackets will also be provided, to adjust and hold the fixture against the drywall ceiling from the top. When linking to another fixture or corner fixture module call us or send a copy of your plan along with your PO and flanges will be removed on those end that needs to make a seamless connection. |
| OPT-SCX-MIF-L | This is a L Module option. |
| OPT-SCX-MIF-T | This is a T Module option. |
| OPT-SCX-MIF-X | This is a X Module option. |
| OPT-SCX-MIF-IC | This is a Inside Corner Module option. |




T-BAR INSTALLATION

| Model | DESCRIPTION |
|------------------|---|
| OPT-SCX-TBAR-4FT | Add this option and 1/2" wide flanges will be installed on the two long sides of the fixture. The two ends of the fixture will fall onto the T-bar grids and will be supported this way. The T-bar tiles on the two sides of the fixture must be cut to allow for the width of the fixture. The tile will fall onto and be supported by the flanges on both sides of the fixture. If you plan to support the fixture by the grids on three sides and tile on one side, call us or specify on your PO, and flange will be installed only on one side of the fixture. To provide safety and support from the beams above the T-bar ceiling order 10ft or 20ft aircraft suspension kits below. |
| SCL-GS10 | Adjustable 1/16" 10ft suspension kit with loop gripper & toggle ends hold up to 70 lbs load. |
| SCL-GS20 | Adjustable 1/16" 20ft suspension kit with loop gripper & toggle ends hold up to 70 lbs load. |
| OPT-FWH-63 | This is a 6FT 3-Wire Whip option. |
| OPT-FWH-65 | This is a 6FT 5-Wire Whip option. |
| OPT-FWH-66 | This is a 6FT 6-Wire Whip option. |



SURFACE MOUNTING


No additional accessories required.
Screw and anchor kit provided with each fixture can be used to fasten the fixture directly to the hard surface through the holes on top of the fixture.



FACTORY-INSTALLED OPTIONS:


LOUVER VERSION

| Model | DESCRIPTION | LUMENS @ 4000K | SIZE |
|-----------------|--|----------------|------|
| OPT-SCX-LUV-4FT | This Louver option includes lens inside. | 4320LM | 4FT |



COLOR OF YOUR CHOICE

| Model | DESCRIPTION |
|--------------------|---|
| OPT-SCX-CLR-4FT | Add this option and specify your desired color on your purchase order or provide a swatch to match. For painted flanged fixture or optional rod, mounting set please also add the relevant option below for each fixture. |
| OPT-SCX-CLR-FRM | This is a painted flanges option. |
| OPT-SCX-CLR-RODSET | This is a painted rod set option. |




INDIRECT (UP) LIGHTING

| Model | WATTS | LUMENS | COLOR TEMP | SIZE |
|-------------------------|--------------------------------------|--------|------------|------|
| OPT-SCX-ULM-4FT-16W-30K | 16W | 1600LM | 3000K | 4FT |
| OPT-SCX-ULM-4FT-16W-35K | 16W | 1648LM | 4000K | 4FT |
| OPT-SCX-ULM-4FT-16W-40K | 16W | 1680LM | 5000K | 4FT |
| OPT-SCX-ULM-4FT-16W-50K | 16W | 1728LM | 6000K | 4FT |
| OPT-SCX-ULM-BU | Indirect (up) light with blue color | | | |
| OPT-SCX-ULM-GR | Indirect (up) light with green color | | | |



EMERGENCY BATTERY BACKUP

| Model | DESCRIPTION |
|---------------|--|
| OPT-EM-CM1INT | This is an option for a 90-minute backup battery installation. If you need to order this series for the fixture, please have your purchase order ready and call us or specify on the order which fixture to install this option and the test button. |





BI-LEVEL MOTION SENSOR

| Model | DESCRIPTION |
|----------------------|---|
| OPT-SCX-SEN2US | This option installs an advanced motion sensor that will turn the lights on when the area is occupied. When the area is cleared, after a preset hold time of 5 sec or more the lights are dimmed to a standby level of 30% or more. If still no motion is detected, after the standby period, the light is turned off. All setting is programmable with a remote control. |
| OPT-WEC-3RC | This is an optional remote control for sensor. |
| OPT-SEN-SCX-2MRLV-5 | This is a programmable microwave Bi-Level sensor. |
| OPT-SEN-2US-DAYLIGHT | It is an ultrasonic Bi-Level Dimming Daylight sensor option for internal installation inside the fixture. (Remote not needed) |




CORNER FIXTURE MODULES:



Built-in LED Modules



| Model | JOINT TYPE | LUMENS | COLOR TEMP | DIMENSION |
|-----------|------------|--------|------------|-------------------------------|
| SCX-L-30K | L | 508LM | 3000K | 5.75" X 5.75" X 3.35" X 2.75" |
| SCX-L-35K | L | 575LM | 3500K | 5.75" X 5.75" X 3.35" X 2.75" |
| SCX-L-40K | L | 616LM | 4000K | 5.75" X 5.75" X 3.35" X 2.75" |
| SCX-L-50K | L | 660LM | 5000K | 5.75" X 5.75" X 3.35" X 2.75" |




| Model | JOINT TYPE | LUMENS | COLOR TEMP | DIMENSION |
|-----------|------------|--------|------------|------------------------------------|
| SCX-T-30K | T | 629LM | 3000K | 7" X 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-T-35K | T | 726LM | 3500K | 7" X 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-T-40K | T | 787LM | 4000K | 7" X 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-T-50K | T | 854LM | 5000K | 7" X 3.35" X 2.75" X 2.15" X 2.15" |




| Model | JOINT TYPE | LUMENS | COLOR TEMP | DIMENSION |
|-----------|------------|--------|------------|-------------------------------|
| SCX-X-30K | X | 733LM | 3000K | 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-X-35K | X | 863LM | 3500K | 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-X-40K | X | 944LM | 4000K | 3.35" X 2.75" X 2.15" X 2.15" |
| SCX-X-50K | X | 1037LM | 5000K | 3.35" X 2.75" X 2.15" X 2.15" |





| Model | JOINT TYPE | LUMENS | COLOR TEMP | DIMENSION |
|------------|---------------|--------|------------|-------------------------------|
| SCX-IC-30K | INSIDE CORNER | 629LM | 3000K | 7.25" X 7.25" X 3.35" X 2.75" |
| SCX-IC-35K | INSIDE CORNER | 726LM | 3500K | 7.25" X 7.25" X 3.35" X 2.75" |
| SCX-IC-40K | INSIDE CORNER | 787LM | 4000K | 7.25" X 7.25" X 3.35" X 2.75" |
| SCX-IC-50K | INSIDE CORNER | 854LM | 5000K | 7.25" X 7.25" X 3.35" X 2.75" |



| Model | JOINT TYPE | LUMENS | COLOR TEMP | DIMENSION |
|--------------|-------------|--------|------------|-----------------------------|
| SCX-C120-30K | 120° CORNER | 508LM | 3000K | 6.1" X 6.1" X 3.35" X 2.75" |
| SCX-C120-35K | 120° CORNER | 575LM | 3500K | 6.1" X 6.1" X 3.35" X 2.75" |
| SCX-C120-40K | 120° CORNER | 616LM | 4000K | 6.1" X 6.1" X 3.35" X 2.75" |
| SCX-C120-50K | 120° CORNER | 660LM | 5000K | 6.1" X 6.1" X 3.35" X 2.75" |

