WMC SERIES

WMC-UDL-RGBW-BK WMC-UDL-RGBW-WH






Customer Name:

Project Name:

Note:

Selection:



4" x 12" x 5-3/4"

Ideal for general site lighting, walkways, and stairways, alleys, loading docks, doorway, pathway and parking areas

eatures

- Finish: Black & White
- Compatible with Westgate Smart App, Amazon Alexa, Amazon Echo, Google Home. Connects via WIFI or Bluetooth
- 7-Year Warranty
- Outdoor UP/Down Light

Technical Specifications

Electrical:

Voltage: 120V AC Power Factor: >0.90 Wattage: 24W Efficacy: 100 LPW

THD: <20%

Lighting:

Dimming: TRIAC Dimming

RGBW: 15 Million Colors + 2700K~5000K White Tuning

Total Lumens: 2400LM

Color Rendering Index: CRI ≥ 80 Beam angle: 45° for each side

Rated life: 70,000 hrs

Mechanical:

- This Fixture is Bluetooth mesh Enabled. Bluetooth mesh networking enables many-to-many (m:m) device communications and is optimized for creating largescale device networks. It is ideally suited for control monitoring and automation solutions that require tens, hundreds or thousands of devices to communicate with one another
- Housing: Die-cast Aluminum & Glass
- Finish: Black & White
- Maximum Ambient Temperature: -68°F to 104°F
- IP Rating: IP44, Suitable for Wet Location
- 7-Year Warranty

Applications:

Ideal for general site lighting, walkways, and stairways, alleys, loading docks, doorway, pathway and parking areas











Photometrics: wmc-udl-rgbw





25 20 15 10 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25 30W 5000K Area 25'x 25' Mounting Height: 9'

BUG Rating: B1-U5-G0

Other Views:

Black Finish:









White Finish:





Front View

Back View



Side View

Front View

Back View

Lens View

Performance Table: wmc-udl-rgbw

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
WMC-UDL-MCT-BK-DT	24W	120V	2400LM	RGBW	B1-U5-G0	100
WMC-UDL-MCT-WH-DT	24W	120V	2400LM	RGBW	B1-U5-G0	100

2

Sample Ordering

Model Light Direction Color Temp. Finish

UDL

BK = Black WH = White

RGBW -

BK = E

Factory-Installed Option:

Blank = No Option For Accessories

OPT-PC-B = FOR 120V-277V PHOTOCELL

OPT-EM-OD1INT = INTERNAL EMERGENCY BACK UP BATTERY

Example:

WMC

1. WMC-UDL-RGBW-WH (FOR WMC 30W UP/DOWN LIGHT RGBW FIXTURE 120V)

2. WMC-UDL-RGBW-WH (FOR WMC 30W UP/DOWN LIGHT RGBW FIXTURE 120V)
OPT-PC-B (FOR 120V-277V PHOTOCELL)

FACTORY-INSTALLED OPTION:





OPT-PC-B FOR 120V-277V PHOTOCELL

OPT-EM-OD1INT INTERNAL EMERGENCY BACK UP BATTERY













- For Setting Up The Light(s), Initial Internet Connection or Mobile Data Is Required.
- After the Initial Setup, Internet Connection is not Necessary Anymore. The lights Can Be Controlled with The Mobile App on The Phone or Tablet. Features Such as Dimming, Changing Colors, Lights Scenes, etc.
 Scheduling Feature Requires Internet Connection.
 Bluetooth Devices Need a Gateway (Sold Separately) In Order to Connect to WiFi Network (Internet)



