





Non-cutoff optics with wide forward throw distribution is ideal for extended spacing to mounting height ratio

DIMENSIONS:

8.5"(W) x 7.25"(H) x 9"(D)



1/2" threaded hubs located on the back, rear, and side of housing for greater mounting versatility. Ideal for 1/2" photoelectric control mounting

WML-30CW-SM
WML-30NW-SM
WML-30WW-SM

LED NON-CUTOFF WALL PACK

Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas. Provides crisp, directional light.

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
WML-30CW-SM	30W	120~277V AC	3300 LM	5000K
WML-30NW-SM	30W	120~277V AC	3200 LM	4000K
WML-30WW-SM	30W	120~277V AC	3100 LM	3000K

ELECTRICAL SPECIFICATIONS:

- Input Wattage: 30W
- Input Voltage: 120-277VAC 50/60Hz
- Input Current: 0.35A Max
- Other wattages: 50W, 60W, 80W and 127W
- Power factor: >0.9

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish (Dark Bronze)
- Operating temperature: -4°F ~ 104°F
- Lifespan: 50000 Hrs.
- IP rating: IP65, Wet Locations
- Borosilicate glass lens will not yellow or fade

LIGHTING SPECIFICATIONS:

- LED type/brand: SMD 3030/ Lumileds LEDs
- Total lumens: 3100 LM, 3200 LM and 3300 LM
- LED Quantity: 36 pieces
- Color temperature: 3000K, 4000K and 5000K
- Color rendering index: >80
- Beam angle: 90°

WARRANTY: 7 years

CERTIFICATIONS: UL

