

WMXPRO-MD-20-60W-MCTP




Customer Name: _____

Project Name: _____

Note: _____

Type: _____



15 1/4"(W) x 9 1/2"(H) x 7 1/2"(D)

Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas.

Features

- ADC12 Aluminum Heat Sink, Outdoor Powder Coating
- Connect One End or Both Ends (Dual Function)
- Multi Power & CCT (Switches are inside fixture)
- 7-year warranty
- Prismatic Borosilicate Glass Lens

Technical Specifications

Electrical:

- Input Wattage: 20/30/50/60W
- Input Voltage: 120-277V AC 50/60Hz
- Input current: 0.6A
- Power factor: >0.9
- Efficacy: 130 LPW

Mechanical:

- ADC12 Aluminum Heat Sink, Outdoor Powder Coating
- Lens: Prismatic Borosilicate Glass Lens
- Same Footprint as Traditional HID Wall Packs
- Four 1/2" Hubs: 1 top, 1 on Each Side, 1 Rear
- Mounting: Wall Mounting
- Operating Temperature: -40°F ~ 104°F
- Lifespan: 70000 Hrs.
- IP rating: IP65, Wet Locations

Lighting:

- Dimming: 0-10V Dimming
- Chip: Lumileds LEDs
- Multi Power & CCT (Switches are inside fixture)
- Total Lumens: 8100LM Max.
- Color Temperature: 3000K/4000K/5000K/5700K
- CRI: >70

Applications:




- Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas.
- Replace existing HID wall packs
- Great for use with photocell

Other Models:

• 30W | 4200LM | WMXPRO-SM-15-30W-MCTP • 80W | 11200LM | WMXPRO-MD-20-80W-MCTP • 120W | 16500LM | WMXPRO-LG-50-120W-MCTP



Photometrics: WMXPRO-MD-20-60W-MCTP



BUG Rating: B2-U3-G3

Area 60'x 65' Mounting Height: 9'


Other Views:



Side View



Front View



Back View

Performance Table: WMXPRO-MD-20-60W-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
WMXPRO-MD-20-60W-MCTP	20W	120-277V	2500LM	3000K 4000K 5000K 5700K	B2-U3-G3	130
			2600LM			
			2700LM			
	30W		2700LM			
			3750LM			
			3900LM			
	50W		4050LM			
			4050LM			
			6250LM			
			6500LM			
			6750LM			
			6750LM			
	60W		7500LM			
			7800LM			
			8100LM			
8100LM						



Sample Ordering

Model	Size	Min. Watt	Max. Watt	Watt/Color Temp.
WMXPRO	MD	20	60W	MCTP

Accessorie:

Blank = No Option For Accessories
 WML-SH2= SHIELD FOR WMXPRO 60W

Factory-Installed Options:

Blank = No Option For Accessories
 OPT-EM-OD3INT= INTERNAL EMERGENCY BACKUP BATTERY
 OPT-SEN-3MRLV-5= PROGRAMMABLE MICROWAVE (BI-LEVEL FOR 80W & UP)
 OPT-PC-B= BUTTON
 OPT-CLR-85= COLOR PAINT
 WEC-8RC= REMOTE CONTROL
 OPT-TRS-T20= TAMPER RESISTANT SCREW

ACCESSORY:



WML-SH2

FACTORY-INSTALLED OPTIONS:



OPT-EM-OD3INT



OPT-PC-B



WEC-8RC



OPT-SEN-3MRLV-5

Example:

1. WMXPRO-MD-20-60W-MCTP
2. WMXPRO-MD-20-60W-MCTP
OPT-EM-OD3INT

(FOR 60W MAX MCTP FIXTURE 120-277V)

(FOR 60W MAX MCTP FIXTURE 120-277V)
 (INTERNAL EMERGENCY BACKUP BATTERY)

Dimensions:



WML-SH2
 SHIELD FOR WMXPRO 120W

